



Advantages

- Low pressure drop media resulting in low energy costs
- Robust construction for reliable operation
- Rigid frame for demanding applications. Fire classified M1

Application: Pre filter for comfort air conditioning applications

Type: Pleated Panel

Frame: Metal

Media: Cotton/Synthetic

Dimensions: Filter front dimensions according EN 15805

Rec. final pressure drop acc. EN 13053: 150 Pa

Maximum airflow: 1,1 x nominal flow

Temperature max: 70°C

RH. max: 100%

Mounting/Frames: Front and side access housings and frames are available



Type	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
Metal	G4	Coarse 65%	592x592x50	3400/55	1,1	2,2
Metal	G4	Coarse 65%	287x592x50	1650/55	0,5	1,7
Metal	G4	Coarse 65%	610x610x50	3600/55	1,2	2,3
Metal	G4	Coarse 65%	305x610x50	1800/55	0,6	1,7
Metal	G4	Coarse 65%	500x500x50	2400/55	0,8	1,7
Metal	G4	Coarse 65%	400x500x50	1900/55	0,6	1,5
Metal	G4	Coarse 65%	500x625x50	3000/55	1,0	2,3

Other dimensions are available on request - All dimensions are nominal