

## NRK 0200-0700

## Reversible air/water heat pump

Cooling capacity 35,5 ÷ 148 kW  
Heating capacity 42,31 ÷ 175 kW

- Water produced up to +65 °C
- Heating operations with external temperatures down to -20 °C
- Optimized for operation in heating mode
- Night mode



### DESCRIPTION

Pompa di calore aria/acqua reversibile Reversible air/water heat pump for air conditioning systems with cold water production for cooling rooms and hot water for heating and/or domestic hot water services, suitable for connection with small or medium users.

It's optimised for use in heating mode, and can be combined not only with low-temperature emission systems such as floor heating or fan coils, but also conventional radiators.

Equipped with inverter compressors, axial fans, external coil with aluminium fins, plate heat exchanger on the side.

The base the structure and the panels are made of steel treated with polyester paint RAL 9003.

### VERSIONS

- A** High efficiency
- E** Silenced high efficiency

### FEATURES

#### Operating field

Working at full load up to -20 °C outside air temperature in winter, and up to 48 °C in summer. Hot water production up to 65 °C.

#### Version with Integrated hydronic kit

Integrated hydronic kit containing the main hydraulic components; available with various configurations to obtain a solution that allows you to facilitate installation.

#### Components

Water filter, flow switch, low and high pressure transducers as standard supply on all units.

#### Condensation control temperature

Fitted as standard with a device for electronic condensation control so that the unit can work even with low temperatures, adapting the air flow rate to the actual system request in order to reduce consumption.

### CONTROL

pCO<sup>5</sup> control type

Microprocessor adjustment, with keyboard and LCD display, for easy consultation and intervention on the unit via a menu available in several languages.

Adjustment includes complete management of the alarms and their log.

Possibility to control two units in a Master-Slave configuration

The presence of a programmable timer allows functioning time periods and a possible second set-point to be set.

The temperature control takes place with the integral proportional logic, based on the water output temperature.

### ACCESSORIES

**AER485P1:** RS-485 interface for supervision systems with MODBUS protocol.

**AERNET:** The device allows the control, the management and the remote monitoring of a Chiller with a PC, smartphone or tablet using Cloud connection. AERNET works as Master while every unit connected is configured as Slave (max. 6 unit); also, with a simple click is possible to save a log file with all the connected unit datas in the personal terminal for post analysis.

**C-TOUCH:** 7", touch screen keyboard, which allows to navigate intuitively among the various screens, allowing to modify the operating parameters and graphically view the progress of some variables in real time.

**MULTICHILLER\_EVO:** Control, switch-on and switch-off system of the single chillers where multiple units are installed in parallel, always ensuring constant flow rate to the evaporators.

**PGD1:** Allows you to control the unit at a distance.

**GP:** Anti-intrusion grid.

**VT:** Antivibration supports

### FACTORY FITTED ACCESSORIES

**DRE:** Electronic device for peak current reduction.

**RIF:** Power factor correction. Connected in parallel to the motor allowing about 10% reduction of input current.

**PRM1:** It is a manual pressure switch electrically wired in series with the existing automatic high pressure switch on the compressor discharge pipe.

### COMPATIBILITY WITH VMF SYSTEM

**For more information about VMF system, refer to the dedicated documentation.**

### ACCESSORIES COMPATIBILITY

Model	Ver	0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
AER485P1	A					*	*	*	*	*	*
	E	*	*	*	*	*	*	*	*	*	*
AERNET	A					*	*	*	*	*	*
	E	*	*	*	*	*	*	*	*	*	*
C-TOUCH	A					*	*	*	*	*	*
	E	*	*	*	*	*	*	*	*	*	*
MULTICHILLER_EVO	A					*	*	*	*	*	*
	E	*	*	*	*	*	*	*	*	*	*
PGD1	A					*	*	*	*	*	*
	E	*	*	*	*	*	*	*	*	*	*

GP: anti-intrusion grid

Ver	0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
A	-	-	-	-	GP2 x 2 (1)	GP2 x 2 (1)	GP2 x 2 (1)	GP2 x 2 (1)	GP2 x 3 (1)	GP2 x 3 (1)
E	GP3	GP3	GP4	GP4	GP2 x 2 (1)	GP2 x 2 (1)	GP2 x 2 (1)	GP2 x 2 (1)	GP2 x 3 (1)	GP2 x 3 (1)

(1) x \_ indicates the quantity to buy.

The accessory cannot be fitted on the configurations indicated with -

VT: Antivibration

Ver	0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Integrated hydronic kit: 00</b>										
A	-	-	-	-	VT11	VT11	VT11	VT11	VT22	VT22
E	VT17	VT17	VT17	VT17	VT11	VT11	VT11	VT11	VT22	VT22
<b>Integrated hydronic kit: 01, 02, 03, 04, 05, 06, 07, 08</b>										
A	-	-	-	-	VT11	VT11	VT11	VT11	VT22	VT22
E	VT13	VT13	VT13	VT13	VT11	VT11	VT11	VT11	VT22	VT22
<b>Integrated hydronic kit: P1, P2, P3, P4</b>										
A	-	-	-	-	VT11	VT11	VT11	VT11	VT22	VT22
E	VT17	VT17	VT17	VT17	VT11	VT11	VT11	VT11	VT22	VT22

The accessory cannot be fitted on the configurations indicated with -

DRE: Device for peak current reduction

Ver	0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
A	-	-	-	-	DRE351 (1)	DRE501 (1)	DRE551 (1)	DRE601 (1)	DRE651 (1)	DRE701 (1)
E	DRE201 (1)	DRE281 (1)	DRE301 (1)	DRE331 (1)	DRE351 (1)	DRE501 (1)	DRE551 (1)	DRE601 (1)	DRE651 (1)	DRE701 (1)

(1) Only for supplies of 400V 3N ~ 50Hz and 400V 3 ~ 50Hz. x 2 or x 3 (if present) indicates the quantity to be ordered.

The accessory cannot be fitted on the configurations indicated with -

A grey background indicates the accessories assembled in the factory

RIF: Power factor correction

Ver	0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
A	-	-	-	-	RIF65	RIF58	RIF59	RIF60	RIF61	RIF61
E	RIF55	RIF56	RIF54	RIF57	RIF65	RIF58	RIF59	RIF60	RIF61	RIF61

The accessory cannot be fitted on the configurations indicated with -

A grey background indicates the accessories assembled in the factory

PRM1: Manually reset pressure switch

Ver	0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
A	-	-	-	-	PRM1	PRM1	PRM1	PRM1	PRM1	PRM1
E	PRM1	PRM1	PRM1	PRM1	PRM1	PRM1	PRM1	PRM1	PRM1	PRM1

The accessory cannot be fitted on the configurations indicated with -

A grey background indicates the accessories assembled in the factory

## CONFIGURATOR

Field	Description
<b>1,2,3</b>	<b>NRK</b>
<b>4,5,6,7</b>	<b>Size (1)</b> 0200, 0280, 0300, 0330, 0350, 0500, 0550, 0600, 0650, 0700
<b>8</b>	<b>Operating field</b>
°	Standard mechanic thermostatic valve (2)
<b>9</b>	<b>Model</b>
H	Heat pump
<b>10</b>	<b>Heat recovery</b>
°	Without heat recovery
D	With desuperheater (3)
<b>11</b>	<b>Version</b>
A	High efficiency
E	Silenced high efficiency
<b>12</b>	<b>Coils</b>
°	Rame - alluminio
R	Copper-copper
S	Copper-Tinned copper
V	Copper-painted aluminium
<b>13</b>	<b>Fans</b>
°	Standard (4)
J	Inverter (5)
M	Oversized (6)
<b>14</b>	<b>Power supply</b>
°	400V 3N ~ 50Hz
<b>15,16</b>	<b>Integrated hydronic kit (7)</b>
00	Without hydronic kit
01	Storage tank with low head pump
02	Storage tank with low head pump + stand-by pump
03	Storage tank with high head pump
04	Storage tank with high head pump + stand-by pump
05	Storage tank with holes for heaters and single low head pump
06	Storage tank with holes for heaters and pump low head + stand-by pump
07	Storage tank with holes for heaters and single high head pump
08	Storage tank with holes for heaters and pump high head + stand-by pump
P1	Single pump low head
P2	Pump low head + stand-by pump
P3	Single pump high head
P4	Pump high head + stand-by pump

(1) The size 0200÷0330 only available in low noise version "E".

(2) Water produced up to +4 °C

(3) The desuperheater must be intercepted in heating mode. In cooling mode, a water temperature no lower than 35°C must always be guaranteed on the heat exchanger inlet.

(4) As standard in sizes from 0350÷0700.

(5) Standard for size 0200÷0330, without useful static pressure. Option for size 0350÷0700 with useful static pressure.

(6) Option available only for size 0200÷0330.

(7) Gli accumuli con fori per resistenze integrative vengono spediti dalla fabbrica con tappi in plastica di protezione, prima del caricamento dell'impianto. Qualora non sia prevista l'installazione di una o tutte le resistenze è obbligatorio sostituire i tappi in plastica con appositi tappi, disponibili comunemente in commercio.

## PERFORMANCE SPECIFICATIONS

NRK - A / 12/7 °C - 40/45 °C

Size		0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Cooling performance 12 °C / 7 °C (1)</b>											
Cooling capacity	kW	-	-	-	-	75,4	88,8	101,6	117,4	133,4	148,1
Input power	kW	-	-	-	-	25,4	29,5	34,4	41,0	45,0	52,6
Cooling total input current	A	-	-	-	-	55,0	61,0	66,0	72,0	87,0	107,0
EER	W/W	-	-	-	-	2,97	3,01	2,95	2,86	2,97	2,82
Water flow rate system side	l/h	-	-	-	-	12983	15278	17488	20211	22975	25516
Pressure drop system side	kPa	-	-	-	-	23	26	32	28	34	42
<b>Heating performance 40 °C / 45 °C (2)</b>											
Heating capacity	kW	-	-	-	-	87,9	103,9	118,9	136,6	155,6	174,4
Input power	kW	-	-	-	-	25,5	30,2	34,7	39,9	45,6	51,7
Heating total input current	A	-	-	-	-	54,0	59,0	64,0	70,0	85,0	106,0
COP	W/W	-	-	-	-	3,45	3,44	3,42	3,42	3,41	3,37
Water flow rate system side	l/h	-	-	-	-	15236	18010	20602	23680	26988	30254
Pressure drop system side	kPa	-	-	-	-	32	36	44	37	45	57

(1) Data 14511:2018; System side water heat exchanger 12 °C/7 °C; External air 35 °C

(2) Data 14511:2018; System side water heat exchanger 40 °C/45 °C; Outside air 7 °C d.b. / 6 °C w.b.

NRK - A / 23/18 °C - 30/35 °C

Size		0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Cooling performance 23 °C/18 °C (1)</b>											
Cooling capacity	kW	-	-	-	-	93,2	108,2	122,7	143,0	165,0	181,0
Input power	kW	-	-	-	-	26,4	30,7	35,9	43,3	47,0	55,1
Cooling total input current	A	-	-	-	-	57,0	63,0	69,0	75,0	90,0	112,0
EER	W/W	-	-	-	-	3,54	3,53	3,42	3,30	3,51	3,28
Water flow rate system side	l/h	-	-	-	-	16111	18705	21231	24719	28513	31266
Pressure drop system side	kPa	-	-	-	-	35	39	47	42	52	63
<b>Heating performance 30 °C/35 °C (2)</b>											
Heating capacity	kW	-	-	-	-	86,4	101,5	114,6	132,6	150,2	170,5
Input power	kW	-	-	-	-	20,6	24,5	27,8	31,7	37,0	41,9
Heating total input current	A	-	-	-	-	44,0	48,0	51,0	55,0	68,0	85,0
COP	W/W	-	-	-	-	4,19	4,15	4,13	4,19	4,06	4,06
Water flow rate system side	l/h	-	-	-	-	14931	17533	19787	22919	25938	29467
Pressure drop system side	kPa	-	-	-	-	31	34	41	35	42	54

(1) Data 14511:2018; System side water heat exchanger 23 °C/18 °C; External air 35 °C  
 (2) Data 14511:2018; System side water heat exchanger 30 °C/35 °C; Outside air 7 °C d.b. / 6 °C w.b.

NRK - E / 12/7 °C - 40/45 °C

Size		0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Cooling performance 12 °C/7 °C (1)</b>											
Cooling capacity	kW	35,6	50,4	59,5	66,1	74,4	87,4	99,8	114,5	130,8	145,3
Input power	kW	11,7	17,4	19,5	22,3	27,6	32,4	38,1	45,8	49,5	58,1
Cooling total input current	A	28,0	38,0	42,0	49,0	60,0	67,0	73,0	72,0	95,0	119,0
EER	W/W	3,05	2,90	3,05	2,96	2,69	2,70	2,62	2,50	2,64	2,50
Water flow rate system side	l/h	6131	8670	10235	11379	12801	15035	17175	19713	22512	25033
Pressure drop system side	kPa	18	17	23	19	22	25	30	27	32	41
<b>Heating performance 40 °C/45 °C (2)</b>											
Heating capacity	kW	42,2	59,7	69,4	78,2	87,9	103,9	118,9	136,6	155,6	174,4
Input power	kW	12,0	17,0	19,9	22,4	25,5	30,2	34,7	39,9	45,6	51,7
COP	W/W	3,50	3,50	3,49	3,49	3,45	3,44	3,42	3,42	3,41	3,37
Heating total input current	A	24,0	34,0	38,0	44,0	54,0	59,0	64,0	70,0	85,0	106,0
Water flow rate system side	l/h	7318	10355	12032	13569	15236	18010	20602	23680	26988	30254
Pressure drop system side	kPa	24	22	30	25	32	36	44	37	45	57

(1) Data 14511:2018; System side water heat exchanger 12 °C/7 °C; External air 35 °C  
 (2) Data 14511:2018; System side water heat exchanger 40 °C/45 °C; Outside air 7 °C d.b. / 6 °C w.b.

NRK - E / 23/18 °C - 30/35 °C

Size		0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Cooling performance 23 °C/18 °C (1)</b>											
Cooling capacity	kW	44,2	61,5	72,1	80,9	91,9	106,5	120,6	139,5	161,7	177,5
Input power	kW	12,2	18,2	20,4	23,5	28,7	33,6	39,7	48,3	51,7	60,8
Cooling total input current	A	29,0	40,0	44,0	51,0	62,0	69,0	76,0	75,0	99,0	124,0
EER	W/W	3,64	3,37	3,53	3,44	3,20	3,16	3,04	2,89	3,13	2,92
Water flow rate system side	l/h	7643	10631	12470	13977	15886	18408	20850	24110	27939	30673
Pressure drop system side	kPa	28	26	34	29	34	37	44	40	49	62
<b>Heating performance 30 °C/35 °C (2)</b>											
Heating capacity	kW	41,4	57,2	67,2	75,7	86,4	101,5	114,6	132,6	150,2	170,5
Input power	kW	9,4	13,3	15,8	18,1	20,6	24,5	27,8	31,7	37,0	41,9
Heating total input current	A	19,0	26,0	30,0	35,0	44,0	48,0	51,0	55,0	68,0	85,0
COP	W/W	4,41	4,31	4,26	4,18	4,19	4,15	4,13	4,19	4,06	4,06
Water flow rate system side	l/h	7156	9895	11628	13083	14931	17533	19787	22919	25938	29467
Pressure drop system side	kPa	23	20	28	23	31	34	41	35	42	54

(1) Data 14511:2018; System side water heat exchanger 23 °C/18 °C; External air 35 °C  
 (2) Data 14511:2018; System side water heat exchanger 30 °C/35 °C; Outside air 7 °C d.b. / 6 °C w.b.

**ENERGY DATA**

Size		0200	0280	0300	0330	0350	0500	0550	0600	0650	0700	
<b>Cooling capacity with low leaving water temp (UE n° 2016/2281)</b>												
SEER	A	W/W	-	-	-	-	3,45	3,52	3,46	3,42	3,44	3,33
	E	W/W	3,40	3,30	3,48	3,39	3,35	3,42	3,34	3,29	3,35	3,27
η <sub>sc</sub>	A	%	-	-	-	-	134,80	137,60	135,20	133,70	134,60	130,00
	E	%	133,00	128,80	136,10	132,50	130,90	133,70	130,60	128,70	130,90	127,90
<b>UE 813/2013 average temperature - Pdesignh ≤ 400 kW (1)</b>												
Pdesignh	A	kW	-	-	-	-	89	106	121	137	157	178
	E	kW	44	62	70	80	89	106	121	137	157	178
SCOP	A		-	-	-	-	2,88	2,90	3,03	3,03	2,93	2,90
	E		3,08	3,03	3,00	3,03	2,88	2,90	3,03	3,03	2,93	2,90
η <sub>sh</sub>	A	%	-	-	-	-	112,00	113,00	118,00	118,00	114,00	113,00
	E	%	120,00	118,00	117,00	118,00	112,00	113,00	118,00	118,00	114,00	113,00

(1) Efficiencies for average temperature applications (55°C)

## ELECTRIC DATA

Size			0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Electric data</b>												
Maximum current (FLA)	A	A	-	-	-	-	75,0	85,0	94,0	114,0	144,0	147,0
	E	A	40,0	49,0	61,0	74,0	75,0	85,0	94,0	114,0	144,0	147,0
Peak current (LRA)	A	A	-	-	-	-	216,0	226,0	191,0	228,0	285,0	288,0
	E	A	124,0	146,0	175,0	215,0	216,0	226,0	191,0	228,0	285,0	288,0


## GENERAL TECHNICAL DATA

Size			0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Compressor</b>												
Type	A	Type	-	-	-	-	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll
	E	Type	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll	Scroll
Compressor regulation	A	Type	-	-	-	-	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off
	E	Type	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off
Number	A	no.	-	-	-	-	2	3	4	4	4	4
	E	no.	2	2	2	2	2	3	4	4	4	4
Circuits	A	no.	-	-	-	-	2	2	2	2	2	2
	E	no.	2	2	2	2	2	2	2	2	2	2
Refrigerant	A	Type	-	-	-	-	R410A	R410A	R410A	R410A	R410A	R410A
	E	Type	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Refrigerant charge	A	kg	-	-	-	-	23,0	28,0	29,0	29,0	39,0	40,0
	E	kg	14,0	16,0	16,0	16,0	23,0	28,0	29,0	29,0	39,0	40,0
<b>System side heat exchanger</b>												
Type	A	Type	-	-	-	-	Plates	Plates	Plates	Plates	Plates	Plates
	E	Type	Plates	Plates	Plates	Plates	Plates	Plates	Plates	Plates	Plates	Plates
Number	A	no.	-	-	-	-	1	1	1	1	1	1
	E	no.	1	1	1	1	1	1	1	1	1	1
<b>Hydraulic connections</b>												
Connections (in/out)	A	Type	-	-	-	-	G.s.	G.s.	G.s.	G.s.	G.s.	G.s.
	E	Type	G.s.	G.s.	G.s.	G.s.	G.s.	G.s.	G.s.	G.s.	G.s.	G.s.
Diametre (in)	A	Ø	-	-	-	-	2½"	2½"	2½"	2½"	2½"	3"
	E	Ø	2½"	2½"	2½"	2½"	2½"	2½"	2½"	2½"	2½"	3"
Diametre (out)	A	Ø	-	-	-	-	2½"	2½"	2½"	2½"	2½"	3"
	E	Ø	2½"	2½"	2½"	2½"	2½"	2½"	2½"	2½"	2½"	3"
<b>Fan</b>												
Type	A	Type	-	-	-	-	axials	axials	axials	axials	axials	axials
	E	Type	axials	axials	axials	axials	axials	axials	axials	axials	axials	axials
Fan motor	A	Type	-	-	-	-	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off
	E	Type	Inverter	Inverter	Inverter	Inverter	On-Off	On-Off	On-Off	On-Off	On-Off	On-Off
Number	A	no.	-	-	-	-	2	2	2	2	3	3
	E	no.	4	6	8	8	2	2	2	2	3	3
Air flow rate	A	m³/h	-	-	-	-	37000	36500	36500	36500	58000	58000
	E	m³/h	14000	20000	26000	26000	21100	21400	22400	22400	31900	31900
<b>Sound data calculated in cooling mode (1)</b>												
Sound power	A	dB(A)	-	-	-	-	82,0	82,0	82,0	83,0	85,0	85,0
	E	dB(A)	74,0	74,0	75,0	75,0	74,0	74,0	74,0	75,0	77,0	77,0
Sound pressure level (10 m)	A	dB(A)	-	-	-	-	50,1	50,1	50,1	51,1	53,0	53,0
	E	dB(A)	42,3	42,3	43,2	43,2	42,1	42,1	42,1	43,1	45,0	45,0

(1) Sound power calculated on the basis of measurements made in accordance with UNI EN ISO 9614-2, as required for Eurovent certification. Sound pressure (cold functioning) measured in free field, 10m away from the unit external surface (in compliance with UNI EN ISO 3744).

G.s. = Grooved joints

## DIMENSIONS



Size			0200	0280	0300	0330	0350	0500	0550	0600	0650	0700
<b>Dimensions and weights</b>												
A	A	mm	-	-	-	-	1875	1875	1875	1875	1875	1875
	E	mm	1606	1606	1606	1606	1875	1875	1875	1875	1875	1875
B	A	mm	-	-	-	-	3330	3330	3330	3330	4330	4330
	E	mm	2700	2700	3250	3250	3330	3330	3330	3330	4330	4330
C	A	mm	-	-	-	-	1100	1100	1100	1100	1100	1100
	E	mm	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100
Weight empty	A	kg	-	-	-	-	1118	1264	1325	1367	1562	1597
	E	kg	804	876	960	967	1118	1264	1325	1367	1562	1597

Aermec reserves the right to make all modification deemed necessary for improving the product at any time with any modification of technical data.

### Aermec S.p.A.

Via Roma, 996 - 37040 Bevilacqua (VR) - Italia  
Tel. 0442633111 - Telefax 044293577  
www.aermec.com