



### ADVANTAGES

- Fast, simple filterchange
- Compact design
- Long lifespan
- High efficiency

<b>Application</b>	Air filter for ventilation units
<b>Type</b>	V-Bank Box Filter
<b>Frame</b>	Galvanised steel
<b>Gasket</b>	Polyurethane, endless foamed
<b>Media</b>	Glass fiber
<b>Separator</b>	Hot-melt
<b>Sealant</b>	Polyurethane
<b>Dimensions</b>	Filter front dimensions according EN 15805
<b>Rec. final pressure drop acc. EN 13053</b>	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
<b>Max airflow</b>	1,1 x nominal flow
<b>Temperature max</b>	70°C
<b>RH. max</b>	100%



Model Name	Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)	ASHRAE 52.2-2017
Opakair	OPR-E-F7	F7	ePM1 55%	610x610x292	4500/85	20	18	MERV 13
Opakair	OPR-E-F7	F7	ePM1 55%	305x610x292	2250/85	10	9	MERV 13
Opakair	OPR-E-F8	F8	ePM1 70%	610x610x292	4500/110	20	18	MERV 14
Opakair	OPR-E-F8	F8	ePM1 70%	305x610x292	2250/110	10	9	MERV 14
Opakair	OPR-E-F9	F9		610x610x292	3400/140	20	18	
Opakair	OPR-E-F9	F9		305x610x292	1700/140	10	9	