

NEW


# AQUARIA SLIM 12 P

AQUARIA SLIM 12 P Code 01957



## FEATURES

- Slim design: Only 190 mm thickness
- Tank capacity: 2,5 lt
- Removable tank: with integrated carrying handle
- Digital control panel
- Humidity and temperature display visualization
- 24 h on-off timer
- Auto Function: sets relative humidity at 60%
- Turbo function: maximum fan speed
- Dry function: continuous dehumidification
- Silent function: minimum fan speed
- Manually adjustable Humidistat
- Continuous draining mode
- Washable antidust filter
- Active carbon filter
- Rear handle
- Practical carrying handles
- Automatic shut-off with full tank
- For rooms up to: 55 m<sup>3</sup>



**SLIM DESIGN**  
Only 190 mm thickness.




**DIGITAL CONTROL PANEL**  
LED display and digital controls.




**REMOVABLE 2.5 L TANK**  
With integrated practical carrying handle.



**PRACTICAL**  
Thanks to the handle and the transportable wheels.



**HUMIDITY AND TEMPERATURE CONTROL**  
Humidity level control and room temperature display



**PURE SYSTEM**  
Anti-dust filter and active carbon filter, for better air quality.

		AQUARIA SLIM 12 P
	Code	01957
	EAN	
Dehumidification capacity (2)		10
Heating capacity		-
Power absorption in dehumidification mode (1)		168
Nominal absorption in dehumidification mode (1)		1,10
Max. power absorption in dehumidification mode (2)		190
Max. absorption in dehumidification mode (2)		1,25
Max. power absorption in dehumidification mode (U.L.U.)		220w
Protection level		IP 20
Fan speeds		2
Tank capacity		2,5L
Air volume ( max )		100
Dimensions ( W x H x D with wheels)		320X490X185 mm
Packing dimensions ( W x H x D)		365x545x245 mm
Noise level		≤45db(A)
Weight (without packing)		10,5
Weight (with packing)		12kg
Refrigerant gas		R290
Global warming potential of refrigerant GWP		3
Global warming potential of refrigerant		-
Refrigerant gas charge		0,050
Minimum floor area for installation, use and storage		4,00
Power cable ( N° pole x section mmq )		3 X 0.75 MM2
Plug		SCHUKO
Power supply		220-240 - 1 - 50
Power supply min - max		207-254
Conformity Mark		CE
Protection level Mark		TUV SUD-GS
Air filter		✓
Carbon filter		✓
Continuous operation with hose		✓
Mechanical humidity level settings		
Electronic humidity level settings		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Laundry function		✓
Timer function		✓
Defrosting device		✓

(1) DB 27°C - WB 21°C ( 27°C - 60% RH )

(2) DB 32°C - WB 29°C ( 32°C - 80% RH )